



*Prestige*

## AUTOMATICA / SEMI AUTOMATICA

- ✓ Erogazione con programmazione delle dosi caffè e acqua calda (modello AUTOMATICO) o erogazione manuale (modello SEMI AUTOMATICO)
- ✓ Carrozzeria in acciaio inox con inserti in lamiera verniciata (nero / bianco / rosso)
- ✓ Lancia vapore/acqua in acciaio inox
- ✓ Sistema di preinfusione elettronica inseribile del caffè (solo versione automatica) e sistema di riscaldamento gruppo con circolazione termosifonica
- ✓ Boiler in rame (Cu 99,5) con trattamento anti-ossidante
- ✓ La bacinella appoggiatazze può essere adattata su due differenti livelli per erogazione espresso o erogazione tall cups
  
- ✓ Automatic coffee and hot water portion control (AUTOMATIC version) or manual portion control (SEMI AUTOMATIC version)
- ✓ Bodywork all stainless steel with painted iron parts (black / white / red)
- ✓ Stainless steel steam and water wands
- ✓ Coffee pre-infusion system (only automatic version) and thermosiphon system
- ✓ Copper boiler (Cu 99,5) with anti-oxidation treatment
- ✓ The drip tray can be set to two different levels to accommodate different size of cups / glasses



| Gruppi                    | LxPxH mm    | Caldaia | Peso   | Potenza | Voltaggio                                 |
|---------------------------|-------------|---------|--------|---------|---|
| Groups                    | WxDxH mm    | Boiler  | Weight | Power   | Voltage                                   |
| 1<br>SEMI / AUTO          | 430x545x520 | 5,0 L   | 38 Kg  | 2000 W  | 220-240 Vac 1N 50-60 Hz                   |
| 2 compatta<br>SEMI / AUTO | 650x545x520 | 6,0 L   | 49 Kg  | 2500 W  | 220-240 Vac 1N 50-60 Hz                   |
| 2<br>SEMI / AUTO          | 725x545x520 | 13,5 L  | 60 Kg  | 3000 W  | 220-240 Vac 1N 380-415<br>Vac 3N 50-60 Hz |
| 3<br>SEMI / AUTO          | 965x545x520 | 20,5 L  | 76 Kg  | 5000 W  | 220-240 Vac 1N 380-415<br>Vac 3N 50-60 Hz |